

US010572072B2

(12) United States Patent Wang et al.

(10) Patent No.: US 10,572,072 B2

(45) **Date of Patent:** Feb. 25, 2020

(54) **DEPTH-BASED TOUCH DETECTION**

(71) Applicant: Apple Inc., Cupertino, CA (US)

(72) Inventors: **Lejing Wang**, Sunnyvale, CA (US); **Daniel Kurz**, Sunnyvale, CA (US)

- (73) Assignee: Apple Inc., Cupertino, CA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 182 days.

- (21) Appl. No.: 15/721,207
- (22) Filed: Sep. 29, 2017

(65) **Prior Publication Data**

US 2019/0102044 A1 Apr. 4, 2019

(51) Int. Cl. G06F 3/042 (2006.01) G06K 9/00 (2006.01) H04N 13/271 (2018.01)

(52) U.S. Cl. CPC *G06F 3/0425* (2013.01); *G06K 9/00087* (2013.01); *H04N 13/271* (2018.05); *G06F*

See application file for complete search history.

3/04842; G06F 3/017

(56) References Cited

U.S. PATENT DOCUMENTS

2012/0326995 A1*	12/2012	Zhang G06F 3/0425
2013/0107010 A1*	5/2013	345/173 Hoiem G06K 9/46
		348/47 Hummel G06K 9/6202
2013/03420/1 A1	12/2013	348/77

OTHER PUBLICATIONS

Du, et al., "A Virtual Keyboard Based on True-3D Optical Ranging," BMVC 2005, doi: 10.5244/C.19.27.

C. Harrison, H. Benko, and A. D. Wilson, "Omnitouch: Wearable multitouch interaction everywhere," In Proceedings of the 24th Annual ACM Symposium on User Interface Software and Technology, UIST '11, pp. 441-450, 2011.

Wilson, Andrew D., "Using a Depth Camera as a Touch Sensor," ITS 2010: Devices & Algorithms, Nov. 7-10, 2010, Saarbrucken, Germany.

* cited by examiner

Primary Examiner — Gerald Johnson
(74) Attorney, Agent, or Firm — Blank Rome LLP

(57) ABSTRACT

Systems, methods, and computer readable media to improve the operation of detecting contact between a finger or other object and a surface are described. In general, techniques disclosed herein utilize a depth map to identify an object and a surface, and a classifier to determine when the object is touching the surface. Unlike the prior art, a measure of the object's "distance" is made relative to the surface and not the camera(s) thereby providing some measure of invariance with respect to camera pose. The object-surface distance measure can be used to construct an identifier or "feature vector" that, when applied to a classifier, generates an output indicative of whether the object is touching the surface. The classifier may be based on machine learning and can be trained off-line before run-time operations are commenced. In some embodiments, temporal filtering may be used to improve surface detection operations.

20 Claims, 7 Drawing Sheets

